

4ft T8 17W Shatterproof Glass Tube Spec Hybrid

Can be used in solely plug and play mode or solely bypass mode

SPECIFICATIONS:

| | |
|-------------------------------------|--|
| WATTAGE: | 17W |
| LISTED: | ETL/CETL/FCC |
| VOLTAGE: | 100VAC-277VAC |
| POWER FACTOR: | 0.9 |
| FREQUENCY: | 50-60Hz |
| LUMENS: | 2,430/2,300LM |
| LUMENS EFFICIENCY: | 142/133LM/W |
| KELVIN (CCT): | 4000K / 5000K (3500K available in special order) |
| THD: | 20% |
| CRI: | 80 |
| IP RATING: | IP20 |
| BEAM ANGLE & BASE: | 270 degree / G13 |
| LENS: | Frosted |
| MATERIALS: | Glass + PC |
| POWER: | Internal Isolation |
| LED CHIPS: | San An |
| LIFE SPAN (HOURS): | 50,000hrs |
| DIMMING COMPATIBLE: | No |
| LENGTH OF WARRANTY: | 5 years |
| PRODUCT LENGTH: | 4ft(1200mm) |
| PRODUCT DIAMETER: | 1in(26mm) |
| WEIGHT: | 180G |
| WORKING ENVIRONMENT: | -20°C to 40°C (-4°F to 104°F) |
| SUGGESTED REPLACEMENT FOR: | Fluorescent Tube 36W |
| PERCENTAGE OF WATTAGE SAVED: | >60% |



Features:

Provides exceptional lighting, energy efficient, and low in maintenance cost. Shatterproof glass Type A & B.

Applications:

T8 Linear Tube retrofits are used in commercial buildings such as hotels, conference rooms, schools, and office buildings.

